

## Operator CALC\_FONC\_INTERP

---

### 1 Goal

---

To build a concept of the type `function` or `fonction_c` starting from a function `FORMULA` to 1 or 2 variables. Can be defined real functions with real variables, complex functions with real variables and tablecloths.

One can also produce a new real or complex function, or a tablecloth by interpolating another standard function in the same way (real, complex or a tablecloth).

The use of `CALC_FONC_INTERP` a tabulation of the formula preliminary to calculation allows. Its use is recommended before any transitory and/or nonlinear analysis for reasons of performances.

The operator is not réentrant, it produces a new function or a tablecloth.

## 2 Syntax

Fr [\*] = CALC\_FONC\_INTERP

```

( ♦ FUNCTION = F / [formula]
/ [formule_c]
/ [function]
/ [fonction_c]
/ [tablecloth]

♦ NOM_RESU = / 'TOUTRESU' , [DEFECT]
/ NR , [K8]

♦ NOM_PARA = Np,

♦ / VALE_PARA = lvale, [l_R]
/ LIST_PARA = will lpara ,

[listr8]

♦ PROL_DROITE = / 'CONSTANT' ,
/ 'LINEAR' ,
/ 'EXCLUDED' , [DEFECT]

♦ PROL_GAUCHE = / 'CONSTANT' ,
/ 'LINEAR' ,
/ 'EXCLUDED' , [DEFECT]

♦ Interpol = / 'FLAX' , [DEFECT]
/ 'LOG' , [l_Kn]
/ 'NOT' ,

♦ NOM_PARA_FONC = npf,

♦ / VALE_PARA_FONC = lvalef, [l_R]
/ LIST_PARA_FONC = lparaf, [listr8]

♦ PROL_DROITE_FONC = / 'CONSTANT' ,
/ 'LINEAR' ,
/ 'EXCLUDED' , [DEFECT]

♦ PROL_GAUCHE_FONC = / 'CONSTANT' ,
/ 'LINEAR' ,
/ 'EXCLUDED' , [DEFECT]

♦ INTERPOL_FONC = / 'FLAX' , [DEFECT]
/ 'LOG' , [l_Kn]
/ 'NOT' ,

♦ INFORMATION = / 1,
[DEFECT] / 2,

♦ TITLE = Ti , [l_Kn]

)

```

If F is one formula to 1 parameter, [\*] = function,  
formula with 2 parameters, tablecloth,  
formule\_c to 1 parameter, fonction\_c,

# Code\_Aster

Version  
default

Titre : Opérateur CALC\_FONC\_INTERP  
Responsable : COURTOIS Mathieu

Date : 18/10/2011 Page : 3/8  
Clé : U4.32.01 Révision :  
ead11ab5c756

tablecloth,  
function,  
fonction\_c,

tablecloth,  
function,  
fonction\_c.

## 3 Operands

### 3.1 Operand FUNCTION

◆ FUNCTION = F

Name of FORMULA (interpretable function (FORMULA Cf [U4.31.05])).

This function can be with one or two variables in the case of the real formulas, with a variable only in the case of the complex formulas.

One can however create a new function respectively ( fonction\_c, tablecloth) starting from a function (respectively fonction\_c, tablecloth) by interpolating the first on a different parameter list. This possibility is primarily used in the macro - orders.

When the type as starter is one formula and that NOM\_PARA\_FONC is provided, the structure of produced data is a tablecloth.

#### Notice

*During the interpolation of a formula with two parameters, one checks coherence between the parameters of the formula and the keywords NOM\_PARA and NOM\_PARA\_FONC. See the example of the paragraph 4.2.*

### 3.2 Operand NOM\_RESU

◇ NOM\_RESU = NR

Indicate the name of the result, function thus created is a function whose value is of name NR (8 characters).

### 3.3 Operand NOM\_PARA

◇ NOM\_PARA = NR

Indicate the name of the parameter of the function or tablecloth. By default, the name of the parameter of the formula or provided function is employed.

### 3.4 Operands VALE\_PARA/LISTE\_PARA

◇ / VALE\_PARA = lvale,

lvale is the list of the values of the parameter.

/ LIST\_PARA = will lpara,

will lpara is the list of the values of the parameter: it is a concept of the type listr8 created previously by the order DEFI\_LIST\_REEL [U4.34.01].

### 3.5 Operands PROL\_DROITE and PROL\_GAUCHE

◇ PROL\_DROITE and PROL\_GAUCHE =

Define the type of prolongation on the right (on the left) of the field of definition of the parameter of the function or tablecloth

`CONSTANT' for a prolongation with the last (or first) value of the function,  
`LINEAR' for a prolongation along the first definite segment (PROL\_GAUCHE) or last definite segment (PROL\_DROITE),  
`EXCLUDED' the extrapolation of the values apart from the field of definition of the parameter is prohibited (in this case if a calculation requires a value of the function out of field of definition, the code will stop in fatal error),

## 3.6 Operand Interpol

◇ Interpol =

Type of interpolation of the function enters the values of the variable or type of interpolation of the tablecloth between the values of the parameter. Behind this keyword one expects a parameter list (two at the most).

'FLAX' : linear,  
'LOG' : logarithmic curve,  
'NOT' : one does not interpolate (and thus the program will stop if one asks for the value of the function for a value of the parameter where it was not defined).

If only one value is given, the interpolation will be identical for the X-coordinates and the ordinates. If two values are given, the first corresponds to the interpolation of the X-coordinates and the second with the interpolation of the ordinates.

## 3.7 Operand NOM\_PARA\_FONC

◇ NOM\_PARA\_FONC = NR

Indicate the name of the variable of the functions defining the tablecloth. When the type as starter is a formula and that this keyword is indicated, then the structure of data produced is a tablecloth.

## 3.8 Operands VALE\_PARA\_FONC/LISTE\_PARA\_FONC

◇ / VALE\_PARA\_FONC = lvale,

lvale is the list of the values of the variable of the functions defining the tablecloth.

/ LISTE\_PARA\_FONC = will lpara,

will lpara is the list of the values of the variable of the functions defining the tablecloth: it is a concept of the type listr8 created previously by the order DEFI\_LIST\_REEL [U4.34.01].

## 3.9 Operands PROL\_DROITE\_FONC and PROL\_GAUCHE\_FONC

◇ PROL\_DROITE\_FONC and PROL\_GAUCHE\_FONC =

Define the type of prolongation on the right (on the left) of the field of definition of the variable of the functions of the tablecloth:

'CONSTANT', 'LINEAR', 'EXCLUDED' the same direction has as previously.

## 3.10 Operand INTERPOL\_FONC

◇ INTERPOL\_FONC =

Type of interpolation of the functions between the values of the variable of the functions defining the tablecloth. Behind this keyword one expects a parameter list (two at the most).

Operation is identical to Interpol.

## 3.11 Operand INFORMATION

◇ INFORMATION =

Specify the options of impression on the file MESSAGE.

- 1: pas d' impression (option by default)
- 2: impression of the parameters plus the list of the first 10 values in the order ascending of the parameter

## 3.12 Operand TITLE

◇ TITLE = Ti

Title attached to the concept produced by this operator [U4.03.01].

## 4 Examples

### 4.1 Case of a function

#### 4.1.1 To define the function FORMULA `sin (T)`

```
IF = FORMULA (NOM_PARA = 'INST',  
             VALE = 'sin (INST) ' )
```

#### 4.1.2 Tabuler `sin (T)` starting from a list of realities

```
DEPI = 2.*pi  
PAS0 = DEPI/200.  
LI1 = DEFI_LIST_REEL (BEGINNING = 0, INTERVALLE=_F (JUSQU_A=DEPI,  
PAS=PAS0), )  
  
SI1 = CALC_FONC_INTERP (FONCTION= IF, LIST_PARA = LI1, NOM_RESU = 'DEPL',  
                        PROL_GAUCHE=' EXCLU', PROL_DROITE=' CONSTANT',  
                        INTERPOL=' LIN', TITRE=' FUNCTION SINUS' )
```

#### 4.1.3 Tabuler `sin (T)` starting from a list of values

```
LI2 = (0. , 0.01, 0.03, 0.04, 0.05, 0.06, 0.07, 0.08, 0.09, 0.10)  
  
SI2 = CALC_FONC_INTERP ( FUNCTION = IF, VALE_PARA = LI2,  
                        NOM_PARA = ' INST',  
                        PROL_GAUCHE = 'EXCLUDED', PROL_DROITE =  
'EXCLUDED',  
                        INTERPOL = 'FLAX', TITLE = 'FUNCTION SINE')
```

### 4.2 Case of a tablecloth

#### 4.2.1 To define the function FORMULA `sin (Omega * T)`

```
IF = FORMULA (NOM_PARA = ('FREQ', 'INST'),  
             VALE = 'sin (2*pi*FREQ*INST) ')
```

#### 4.2.2 Tabuler `sin (Omega * T)` starting from a list of moments

The parameter of the tablecloth is 'FREQ', the variable of the functions defining the tablecloth is 'INST'. One checks in CALC\_FONC\_INTERP that the first parameter of the formula is the same one as NOM\_PARA, and that the second parameter of the formula is identical to NOM\_PARA\_FONC.

```
LI_FREQ = DEFI_LIST_REEL (BEGINNING = 10, INTERVALLE=_F (JUSQU_A= 100, PAS  
=10), )  
LI_INST = DEFI_LIST_REEL (BEGINNING = 0, INTERVALLE=_F (JUSQU_A= 100, PAS  
=1), )  
  
SI1 = CALC_FONC_INTERP ( FUNCTION= IF,  
                        NOM_RESU = 'DEPL',  
                        NOM_PARA_FONC=' INST',  
                        LIST_PARA_FONC = LI_INST  
                        PROL_GAUCHE_FONC=' EXCLU',  
                        PROL_DROITE_FONC=' CONSTANT',  
                        INTERPOL_FONC=' LIN',  
                        NOM_PARA=' FREQ',
```

```
LIST_PARA = LI_FREQ  
PROL_GAUCHE=' LINEAIRE',  
PROL_DROITE=' LINEAIRE',  
INTERPOL=' LIN',  
TITRE=' FUNCTION SINUS',)
```