

## Operator LIRE\_FONCTION

---

### 1 Goal

---

To see a data file containing of the actual values representing a function. Product a concept of the type `function` [U4.31.02] or `tablecloth` [U4.31.03].

## 2 Syntax

```

F [function] = LIRE_FONCTION (
    ◆ UNIT = U, [I]
    ◇ FORMAT = 'FREE', [DEFECT]
    ◇ SEPAR = / 'Nun', [DEFECT]
                / '\',
                / '\;',
                / '\',
    ◆ NOM_PARA = cf keyword are equivalent of DEFI_FONCTION
[U4.31.02],
    ◇ NOM_RESU = cf keyword are equivalent of DEFI_FONCTION
[U4.31.02],
    ◇ Interpol = idem
    ◇ PROL_DROITE = idem
    ◇ PROL_GAUCHE = idem
    ◇ VERIF = idem
    ◇ TITLE = idem
    ◇ INFORMATION = idem
    ◇ INDIC_PARA = / [1.1], [DEFECT]
                / [indice1, indice2]
    ◇ TYPE = / 'FUNCTION', [DEFECT]
            / 'FONCTION_C',
            / 'TABLECLOTH',
    if TYPE=' FONCTION':
    ◇ INDIC_RESU = / [1.2], [DEFECT]
                / [indice1, indice2]
    if TYPE=' FONCTION_C':
    ◇ FORMAT_C = / 'REEL_IMAG' [DEFECT]
                / 'MODULE_PHASE',
    if FORMAT_C=' REEL_IMAG':
    ◆ INDIC_REEL = / [1.2], [DEFECT]
    ◆ INDIC_IMAG = / [1.3], [DEFECT]
    if FORMAT_C=' MODULE_PHASE':
    ◆ INDIC_MODU = / [1.2], [DEFECT]
    ◆ INDIC_PHAS = / [1.3], [DEFECT]
    if TYPE=' NAPPE':
    ◆ NOM_PARA_FONC = cf keyword NOM_PARA
    ◆ INDIC_ABSCISSE = [indice1, indice2], [I_I]
    ◇ INTERPOL_FONC = cf keyword INTERPOL
    ◇ PROL_DROITE_FONC = cf keyword PROL_DROITE
    ◇ PROL_GAUCHE_FONC = cf keyword PROL_GAUCHE
    ◇ DEFI_FONCTION = _F (
        ◆ INDIC_RESU = [indice1, indice2], [I_I]
    )
)

```

## 3 Operands

### 3.1 Operand UNIT

◆ UNIT = U

Entirety, logical number of the unit of reading, defining the file in which the data are read.

### 3.2 Operand FORMAT

◇ FORMAT = 'FREE',

This keyword is for the moment useless. It will be able in the future to make it possible to define a format of specific reading, more constraining than the current format.

### 3.3 Operand SEPAR

◇ SEPAR = 'Nun' or ',' or ';' or '/'

Separating character of the columns of figures in the file with reading.

The value by default 'Nun' means one or more white characters. For the other separators, white characters are tolerated between the figures and the separator itself.

### 3.4 Operands PROL\_DROITE / PROL\_GAUCHE/NOM\_PARA/NOM\_RESU/INTERPOL/VERIF/TITLE/INF ORMATION

The digital values are read in the file indicated, then the function is actually created by LIRE\_FONCTION while calling DEFI\_FONCTION or DEFI\_NAPPE.

Thus, these keywords are taken again with identical DEFI\_FONCTION or DEFI\_NAPPE and allow to specify the characteristics of the produced function: interpolation, prolongations, names of the parameters of access.

### 3.5 Operand INDIC\_PARA

◇ INDIC\_PARA = / [indice1, indice2]

This keyword is identical in its principle to the keyword VALE\_PARA order DEFI\_FONCTION. It makes it possible to choose the column of figures in the file read which will define the X-coordinates of the function, are the values of the parameter.

One expects obligatorily a list of two entireties: the first indicating the number of 'block' in the file (cf paragraph [§4] Examples), the second indicating the number of the column. To identify the blocks of the file, one regards as separator of blocks any line which would not exclusively contain figures and separators of columns. The columns are defined by the presence of separators of columns delimiting them (keyword SEPAR).

The value by default is [1.1]: the first column of the first block is read. That makes it possible to define very easily, by informing less possible keywords, the reading of a function in a file containing two simple columns of figures.

### 3.6 Operand TYPE

◇ TYPE = / 'FUNCTION', [DEFECT]  
/ 'FONCTION\_C',  
/ 'TABLECLOTH',

Specify the type of function read and created: 'FUNCTION', 'FONCTION\_C' (call in the macro - order with DEFI\_FONCTION) or 'TABLECLOTH' (call to DEFI\_NAPPE).

## 3.7 Case of a real function: TYPE=' FONCTION '

◇ INDIC\_RESU = / [indice1, indice2]

Of operation identical to INDIC\_PARA, this keyword makes it possible to choose the column of figure in the file read defining the ordinates of the function, are the values of the result.

The value by default is [1.2]: the second column of the first block is read.

## 3.8 Case of a complex function: TYPE=' FONCTION\_C '

◇ FORMAT\_C = 'REEL\_IMAG'  
◆ INDIC\_REEL = / [indice1, indice2]  
◆ INDIC\_IMAG = / [indice1, indice2]

◇ FORMAT\_C = 'MODULE\_PHASE'  
◆ INDIC\_MODU = / [indice1, indice2]  
◆ INDIC\_PHAS = / [indice1, indice2]

In the case of a complex function, two columns of figures (actual values) are to be identified in the file read to define the list of the complex values of the result. One can thus read with the imaginary choice left real/left or modulates/phase. The phase is expressed in radian.

The values by default are respectively [1.2] and [1.3]: the second and third columns of the first block are read. The first column read by default having been the value of the parameter (INDIC\_PARA).

## 3.9 Case of a tablecloth: TYPE=' NAPPE '

◆ NOM\_PARA\_FONC = cf keyword NOM\_PARA  
◆ INDIC\_ABSCISSE = [indice1, indice2],  
◇ INTERPOL\_FONC = cf keyword Interpol  
◇ PROL\_DROITE\_FONC = cf keyword PROL\_DROITE  
◇ PROL\_GAUCHE\_FONC = cf keyword PROL\_GAUCHE  
◇ DEFI\_FONCTION = \_F (  
◆ INDIC\_RESU = [indice1, indice2],

The principle is the same one as that of DEFI\_NAPPE [U4.31.03]: the list of possible values of the parameter (second variable) having been defined by INDIC\_PARA, it remains to identify the functions in the file read by the keyword factor DEFI\_FONCTION (analogue with the keyword factor FUNCTION of DEFI\_NAPPE). Attention, the number of identified functions (occurrences of the keyword factor) will have to be identical to the cardinal of the values read by INDIC\_PARA.

Contrary to the tablecloths in general, one imposes that the functions divide the same list of values of X-coordinates INDIC\_ABSCISSE, this is why only INDIC\_RESU is present under the keyword factor DEFI\_FONCTION.

Keywords '\_FONC' apply to the functions of the tablecloth (cf. DEFI\_NAPPE, keyword factor DEFI\_FONCTION [U4.31.03]).

## 4 Examples of use

That is to say the textual file following containing information to reading. It is composed of columns of figures, here separated by white characters, defining blocks, themselves delimited by free text.

Any line including of other characters that figures and the preset separator is regarded as free text delimiting. There are thus 4 blocks in the following file:

```
aaa bbb ccc
ddd
eee FF
0.      0.      0.
0.1     1.      10.
0.2     2.      20.
0.3     3.      30.
xxx yyy
www zzz
0.4     4.      40.      400.
0.5     5.      50.      500.
0.6     6.      60.      600.
xxx
70.     700.
80.     800.
90.     900.
PPP qqg
8.8
9.9
```

### 4.1 Reading of a simple function

By exploiting the values by default for the choice of the columns:

```
F=LIRE_FONCTION ( UNIT = 38,
                  NOM_PARA = 'INST', )
```

The function thus created is:

X-coordinates = [0. , 0.1,0.2,0.3]

Ordinates = [0. , 1. , 2. , 3. ]

While associating for X-coordinates and ordinates of the columns taken in different blocks:

```
F=LIRE_FONCTION ( UNIT = 38,
                  NOM_PARA = 'INST',
                  INDIC_PARA = [2.4],
                  INDIC_RESU = [3.1],
```

The function thus created is:

X-coordinates = [400. , 500. , 600.]

Ordinates = [ 70. , 80. , 90.]

Attention, the order checks whereas the cardinals of the columns defined by INDIC\_PARA and INDIC\_RESU are quite identical. What would not have been the case here with for example INDIC\_PARA = [1.3].

## 4.2 Reading of a complex function

By exploiting the values by default for the choice of the columns:

```
F=LIRE_FONCTION ( UNIT = 38,  
                  NOM_PARA = 'INST',  
                  TYPE = 'FONCTION_C',  
                  FORMAT_C = 'REEL_IMAG', )
```

The function thus created is:

X-coordinates = [0. , 0.1,0.2,0.3]

Ordinates = [(0. , 0.), (1. , 10.), (2. , 20.), (3. , 30.)]

One could of course have specified other columns for INDIC\_REEL and INDIC\_IMAG that those by default. Attention however to point on columns in the same way cardinal.

## 4.3 Reading of a tablecloth

By exploiting the values by default for the choice of the columns:

```
F=LIRE_FONCTION ( UNIT = 38,  
                  NOM_PARA = 'INST',  
                  INDIC_PARA = [4.1],  
                  NOM_PARA_FONC = 'FREQ',  
                  INDIC_ABSCISSE = [2.2],  
                  DEFI_FONCTION = ( F ( INDIC_RESU = [3.1], ),  
                                     F ( INDIC_RESU = [2.3], ), ) )
```

The tablecloth thus created is:

For the value of parameter INST=8.8, the function:

X-coordinates = [4. , 5. , 6.]

Ordinates = [70. , 80. , 90.]

For the value of parameter INST=9.9, the function:

X-coordinates = [4. , 5. , 6.]

Ordinates = [40. , 50. , 60.]

The checks of coherence of the cardinals of columns of X-coordinates and ordinates are made by the order.