Méthodes Python de pilotage de GMSH

Résumé :

Ce document présente le superviseur permettant de piloter GMSH depuis Python, et donc depuis le fichier de commandes Aster.

Ce superviseur produit tout type de maillages 2D en utilisant le logiciel GMSH (www.geuz.org/gmsh). Il est notamment utilisé dans Aster par l'outil de post-traitement interactif STANLEY afin de générer des éléments de maillage pour le post-traitement, mais peut être étendu à d'autres applications : maillage paramétrique, remaillage, etc.

Document diffusé sous licence GNU FDL (http://www.gnu.org/copyleft/fdl.html)

1 Mode d'emploi

Il y a quatre étapes à suivre pour produire un maillage avec le superviseur GMSH :

1) Définition de la géométrie ;
2) Définition des discrétisations ;
3) Création du maillage GMSH et des GROUP_MA et objets « Physical » associés ;
4) Importation du maillage GMSH dans Aster.

Exemple simple d'utilisation :

Dans l'exemple suivant, on utilise les fonctionnalités du superviseur pour générer le maillage d'une plaque rectangulaire :

Géométrie

```
  from Utilitai.sup_gmsh import *

  larg = 5.
  H_beton = 3.
  H_S1 = 4.
  t_beton   = 25.
  prog_S1 = 1.1
```

On importe le module et on définit quelques paramètres.

```
# Geometrie
  O = Point(0   ,  0      )
  A = Point(larg,  0      )
  B = Point(larg,  H_beton)
  C = Point(0   ,  H_beton)
  D = Point(0   , -H_S1  )
  E = Point(larg, -H_S1  )

  OA = Line(O,A)
  AB = Line(A,B)
  BC = Line(B,C)
  OC = Line(O,C)

  OD = Line(O,D)
  DE = Line(D,E)
  AE = Line(A,E)

  S2 = Surface(OA,AB,BC,OC)
  S1   = Surface(OD,DE,AE,OA)
```


Document diffusé sous licence GNU FDL (http://www.gnu.org/copyleft/fdl.html)

On crée des points, des lignes entre les points et des surfaces à partir des lignes.

```
# Discretisation
  OA.Transfinite(1)
  BC.Transfinite(1)
  DE.Transfinite(1)

  N_beton = int(H_beton/t_beton + 0.5)
  AB.Transfinite(N_beton)
  OC.Transfinite(N_beton)

  N_S1 = Progress(H_S1, r=prog_S1, h=t_beton)
  OD.Transfinite(N_S1,prog_S1)
  AE.Transfinite(N_S1,prog_S1)

  S2.Transfinite()
  S1.Transfinite()
```

On définit la discrétisation des lignes et des surfaces.

```
 # Maillage
  mesh = Mesh()
  mesh.Physical('FOND',DE)
  mesh.Physical('LAT_G',OC,OD)
  mesh.Physical('LAT_D',AB,AE)
  mesh.Physical('INTERFAC',OA)
  mesh.Physical('HAUT',BC)
  mesh.Physical('S2',S2)
  mesh.Physical('S1',S1)
```

On crée l'objet maillage et on définit les groupes de mailles qui seront des GROUP_MA dans la SD maillage Aster et des « *Physical »* dans GMSH (ces derniers seront nommés $GM1$, $GM2$, etc...).

```
MA = mesh.LIRE_GMSH(
                    MODI_QUAD = 'OUI'
                    )
```

Importation du maillage dans Aster : MA est un maillage Aster.

Document diffusé sous licence GNU FDL (http://www.gnu.org/copyleft/fdl.html)

2 Liste des fonctions disponibles

La liste des fonctions est extraite directement du source, `sup_gmsh.py`, ce qui explique qu'elle soit en anglais.

2.1 Classe générique pour les objets géométriques

```
class Geometric :


    private attribute
    parameters    : dictionnary of the attributes (except relation and
parameters itself)
                    see __getattr__ and __setattr__

    Attributes
     num          : index among gmsh objects
     md           : mesh descriptor
     mesh         : related mesh object
     relation     : model object in case of coincidence


    Public methods
     Is_point : return true is the object inherits of the Point class

     Is_line  : return true is the object inherits of the Line class

     Is_surface : return true is the object inherits of the Surface class

     Is_volume : return true is the object inherits of the Volume class

        Is_same_dimension : return true is both objects are of the same
dimension
                            (point, line, surface or volume)
       in -> object to compare to self

     Duplicate   : duplicate an object and base its mesh_descriptor
                   on the mesh_descriptor of the model

     Coincide    : assert that an object is coincident with a model one
                   All the attributes are then automatically read from
                   the model object (see __setattr__ and __getattr__).
       in -> model object


    Private method

     Root :
        Provides the root object of an object, ie the object itself if there
is no relation
       or the deepest model in case of relation.

     Geometric_coincide : check if a geometrical coincidence is possible
                              return information about the coincidence, false
else.
       in -> model object
```


Document diffusé sous licence GNU FDL (http://www.gnu.org/copyleft/fdl.html)

```
        Deep_coincide : proceed recursively to ensure coincidence of the
relevant sub-objects
       in -> model object
       in -> correspond (information returned by Geometric_coincide)

     __setattr__ : distinguish two sets of attributes
                    relation (to express a relation with a model object in
case of coincidence)
                         all the other attributes which are stored in the
dictionnary parameters
                     instead of the usual __dict__ if there is no relation
(see Coincide)
                   and in the model object if there is a coincidence

     __getattr__ : if the object is related (relation <> None) the attribute
is read
                      in the model object. Else, it is read in the current
object, actually
                   in the dictionnary parameters (see __setattr__)

     Thanks to these two overloaded methods, the access to the attributes is
usual if
      there is no relation whereas the attributes of the model object are
accessed
     transparently if there is a relation .

     __cmp__ :
       The comparison of two objects involves possible coincidence. It is no
more the object ids
       that are compared but the object roots (.relation if any).

     Gmsh  : produce the source code for Gmsh
       in -> mesh

     Gmsh_send : send a line code to the gmsh interpreter
       in -> line_code (string)

      Intermediate_meshing : produce the source code for the intermediate
objects
       in -> mesh

     Object meshing : produce the source code for the current object
       var -> object number (modified if several objects are created)
```

2.2 Fonctions pour les objets POINT

```
class Point(Geometric) :

    Public methods
     __init__ :
       in -> coordinates (the 3rd is zero by default)

     Size  : set the size of the neighbouring elements
       in -> size

     Attractor : define the point as an attractor
       in -> scale_x : size amplification factor in the x-direction
       in -> scale_y : size amplification factor in the y-direction
       in -> distance: influence distance for the perturbation
```


Document diffusé sous licence GNU FDL (http://www.gnu.org/copyleft/fdl.html)

```
Attributes
 coor : coordinates
 size : neighbouring element size
 attractor : parameters of the attractor
```


Document diffusé sous licence GNU FDL (http://www.gnu.org/copyleft/fdl.html)

2.3 Fonctions pour les objets LIGNE

```
class Line(Geometric) :

    LINE OBJECT

    Public methods

     Attractor : define the point as an attractor
       in -> scale_x : size amplification factor in the x-direction
       in -> scale_y : size amplification factor in the y-direction
       in -> distance: influence distance for the perturbation


class Circle(Line) :

    CIRCLE OBJECT


def Curve(l_x,l_y,l_z=None) :

    CURVE OBJECT (in -> list of points)
```

2.4 Fonctions pour les objets SURFACE

```
class Surface(Geometric) :

    SURFACE OBJECT (inherit from the Geometric class)

    Public methods
     __init__ :
          in -> lines : external bounday of the surface (lines should be
connected)

     Holes : set the internal holes (surfaces)
       in -> holes : list of holes

      Boundary : checks that the boundary is a closed loop and returns the
orientation of the edges

     Ruled : declare the surface is a ruled one

     Translate : translate the surface
       in -> tran : (numpy) vector of translation

     Recombine : recombine the surface (try to mesh with quadrangles instead
of triangles)

     Transfinite : Declare the mesh to be transfinite


    Attributes
     lines : list of external boundary lines
     holes : list of internal holes (surfaces)
     ruled : indicates (false or true) if the surface is a ruled surface
```


Document diffusé sous licence GNU FDL (http://www.gnu.org/copyleft/fdl.html)

```
        loops : list of boundary (external and internal) loops (computed when
    meshing)
```


Document diffusé sous licence GNU FDL (http://www.gnu.org/copyleft/fdl.html)

2.5 Fonctions pour les opérations sur les maillages

```
class Mesh_Descriptor :

    Attributes
      relation     Another mesh descriptor provides the mesh parameters
      parameters   dictionnary of the mesh parameters
                        size         Point size
                        transfinite  Transfinite mesh (0 or 1)
                             number        Number of elements along a line
(transfinite)
                                  progression   Progression of element size
(transfinite)
                        recombine    Recombine mesh or not

     Specific access :
       md.parameter_name = xxx -> the relation is destroyed (set to None)
       xxx = md.parameter_name -> if there is a relation, the effective
                                  parameter is looked for recursively

     Deep copying : a relation is set to the model instead of a true copy

class Mesh :
  def __init__(self, algo = 2, gmsh='gmsh') :

  def Physical(self, name, *l_obj) : creation of Physical (GMSH object)

  def Save(self, file = 'fort.geo') : save the geo file

  def View(self) : launch GMSH with the current geo file

  def Create(self, file = 'fort.19') : save the geo file and create the msh
file

   def Name(self, MA, CREA_GROUP_NO ) : create the group_ma and/or the
group_no

  def LIRE_GMSH (self,
    UNITE_GMSH     = 19,
    UNITE_MAILLAGE = 20,
    MODI_QUAD      = 'NON' ,
    CREA_GROUP_NO  = 'OUI'
    ) :
```

Lecture du maillage (format Aster) à partir de sa définition (format `sup_gmsh`)
`UNITE_GMSH` = Numéro d'unité logique pour le fichier msh
`UNITE_MAILLAGE` = Numéro d'unité logique pour le fichier mail
`MODI_QUAD` = `'OUI'` si line->quad, `'NON'` sinon
`CREA_GROUP_NO` = `'OUI'` si on crée les `GROUP_NO`, `'NON'` sinon

2.6 Fonctions pour les transformations géométriques

```
def VectorProduct(u,v) :

def VectorNorm(u) :

class Rotation :
```


Document diffusé sous licence GNU FDL (http://www.gnu.org/copyleft/fdl.html)

```
in -> A,C,B
```


Document diffusé sous licence GNU FDL (http://www.gnu.org/copyleft/fdl.html)